

# HEINZMANN Configuration Suite

Including driver (PCAN-USB interface, USB to RS-232 converter with FTDI chip, USB to RS-232 converter with Prolific chip) and XML support (German, English), for Windows 7 or higher.

The use of this software product requires availability of the dashboard files compatible with your device.

## Revision History

### Version 1.1.9

#### Dashboard

- ▶ Parameter and firmware files are accepted by Drag & Drop
- ▶ Improved handling of "Conditions"
- ▶ Improved handling of wrong assignments
- ▶ Various bug fixes

#### Minor bug fix, changes and additions in various windows

### Version 1.1.8

#### Dashboard

- ▶ Bug fix in opening dashboards

### Version 1.1.7

#### Window „Curve over time and X“

- ▶ Bug fixes

#### Dashboard

- ▶ Minor changes and bug fixes

#### Window „Data logger“

- ▶ Date and time format can be changed before a file name is generated to save data from the data logger
- ▶ Saved data logger data will not be deleted when loading a new control unit program

#### Bug fixes in „Load parameter values“

#### Updated control components

#### Updated drivers

# Revision History

## Version 1.1.5

### New Text Parameters Type

- ▶ Text parameter value can be used to store text information, for example, the user can add descriptions, names, addresses, etc. (Latin and numbers are allowed)

### Dashboard

- ▶ New visualization element ‚Slider‘- adjusts the value of a variable, depending on the position of the slider within the slider bar
- ▶ Display of parameters in Anglo-American units is improved

### Communication

- ▶ The ability to show extended information about network participants in the „Devices in Network“ window is added

### Window Map

- ▶ The table data can be quickly copied from the Excel to the buffer and pasted to the DcDesk Map with a key combination Ctr + C

### Window Session Info

- ▶ Parameter configuration file can be managed via popup menu

### Window Curve versus Time

- ▶ Bug fix

### Minor bug fix, changes and additions in various windows

### Updated control components

### Updated drivers for dongle

## Version 1.1.2

### General optimizations and bug fixes

# Revision History

## Version 1.1.0

### New Window Data Logger

- ▶ New window that enables the configuration for the recording of parameter values (Logging) in the control unit and recording management.

### Help file

- ▶ New chapter Data Logger is added

### Windows Curve versus Time and X

- ▶ Stop lines can be hidden - useful if pauses occur frequently in recordings
- ▶ Crosshair and zoom function improved

### General

- ▶ Expanded port configuration for PHLOX und PHLOX III

Added new systems: „Cargo Power Display“ and “DynConnect“

### Minor bug fix

## Version 1.0.31

### Help file

- ▶ Help file has been expanded

### Parameter save/load

- ▶ DcDesk allows saving/loading of parameter values only in format \*.hzm or \*.hzc

### Window Curve

- ▶ New curve type is added: polar diagram

### CAN communication

- ▶ Correct log out from CAN network in the event of disconnection or loss of network

### Changes and additions in various windows

- ▶ Window Dashboard: help function is added
- ▶ Window CAN Device Selection
- ▶ Windows Curve versus time and X

### Updated control components